

Conduit Connector 90°



Standard: UL 514B and C22.2 No. 18.3-12
Material: Zinc
Application: for use to bond Rigid or IMC conduit to a box or enclosure when 90 degree turns are needed

EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
90631	3/4"	1	150	1.732	0.985
90632	1"	1	100	1.969	1.258
90633	1-1/4"	1	50	2.362	1.595


Service Entrance Cap Clamp Type



Standard: UL 514B and C22.2 No. 18.3-12
Material: Aluminum
Application: for use to bring overhead electrical service into buildings

EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
SEC01	1/2"	1	125	2.615	2.000
SEC02	3/4"	1	100	2.752	2.368
SEC03	1"	1	75	3.246	2.621
SEC04	1-1/4"	1	50	3.248	3.000
SEC05	1-1/2"	1	50	4.752	3.312
SEC06	2"	1	20	6.000	4.618
SEC07	2-1/2"	1	4	7.500	6.000
SEC08	3"	1	4	9.000	8.000
SEC10	4"	1	4	9.000	8.000

Service Entrance Cap Threaded Type



Standard: UL 514B and C22.2 No. 18.3-12
Material: Aluminum
Application: for use to bring overhead electrical service into buildings

EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
SEC11	1/2"	1	125	2.610	2.000
SEC12	3/4"	1	100	2.715	2.368
SEC13	1"	1	75	3.108	2.621
SEC14	1-1/4"	1	50	3.220	3.000
SEC15	1-1/2"	1	50	4.351	3.312
SEC16	2"	1	20	5.442	4.618
SEC17	2-1/2"	1	4	7.805	6.000
SEC18	3"	1	4	8.021	8.000
SEC20	4"	1	4	8.510	8.000